

DIMENSIONAL DATA

Platform Height - Elevated	26' / 7.92 m
Platform Height - Lowered	49.5" / 1.26 m
Platform Railing Height	43.3" / 1.10 m
Overall Height	7' 8.8" / 2.36 m
Overall Height - With Rails Folded	6' 5.5" / 1.97 m
Platform Dimensions	44 x 98.5" / 1.12 x 2.5 m
Platform Dimensions - Platform Extension	50" / 1.27 m
Overall Length	8' 2.5" / 2.5 m
Overall Width	46" / 1.17 m
Wheelbase	6' 10" / 2.09 m
Ground Clearance	5" / 127 mm
Platform Capacity	454 kg
Platform Capacity - Capacity on Extension	113 kg
Rail Type	Fold Down
Lift/Lower Time	40/40 seconds
Maximum Drive Height	26' / 7.92 m
Weight* (ANSI/CSA)	2,163 kg
Ground Bearing Pressure	87 psi / 6.11 kg/cm ²

* Certain weights and dimensions may vary due to options and to compliance with country standards.

POWER SYSTEM/CHASSIS

Batteries	4 x 6V, 220 amp-hr
Charger	20 Amp Automatic / 120V/240V - 50/60 Hz
Drive	24V Electric / 8 hp
Pump	Fixed Displacement Gear
Hydraulic Reservoir	6.4 L

PERFORMANCE DATA

Drive Speed, Lowered	2.5 MPH (4.00 kmph)
Drive Speed, Elevated	0.5 MPH (0.8 kmph)
Gradeability	25%
Turning Radius - Inside	Zero
Turning Radius - Outside	95.1" / 2.41 m
Tire Size	16 x 5" / 406 x 125 mm
Tyre Type	Non-Marking Solid
Brakes (on drive wheels)	Electric, Friction



SHERRIN
Rentals
AUSTRALIA WIDE
132 138

Email - info@sherrinrentals.com.au Web - www.sherrinrentals.com.au

26 Foot Scissor Lift