

DIMENSIONAL DATA

| | |
|---|----------------------------------|
| Platform Height - Elevated | 26' / 7.92 m |
| Platform Height - Lowered | 49.5" / 1.26 m |
| Platform Railing Height | 43.3" / 1.10 m |
| Overall Height | 7' 8.8" / 2.36 m |
| Overall Height - With Rails Folded | 6' 5.5" / 1.97 m |
| Platform Dimensions | 44 x 98.5" / 1.12 x 2.5 m |
| Platform Dimensions - Platform Extension | 50" / 1.27 m |
| Overall Length | 8' 2.5" / 2.5 m |
| Overall Width | 46" / 1.17 m |
| Wheelbase | 6' 10" / 2.09 m |
| Ground Clearance | 5" / 127 mm |
| Platform Capacity | 454 kg |
| Platform Capacity - Capacity on Extension | 113 kg |
| Rail Type | Fold Down |
| Lift/Lower Time | 40/40 seconds |
| Maximum Drive Height | 26' / 7.92 m |
| Weight* (ANSI/CSA) | 2,163 kg |
| Ground Bearing Pressure | 87 psi / 6.11 kg/cm ² |

* Certain weights and dimensions may vary due to options and to compliance with country standards.

POWER SYSTEM/CHASSIS

| | |
|---------------------|--|
| Batteries | 4 x 6V, 220 amp-hr |
| Charger | 20 Amp Automatic / 120V/240V - 50/60 Hz |
| Drive | 24V Electric / 8 hp |
| Pump | Fixed Displacement Gear |
| Hydraulic Reservoir | 6.4 L |

PERFORMANCE DATA

| | |
|--------------------------|------------------------|
| Drive Speed, Lowered | 2.5 MPH (4.00 kmph) |
| Drive Speed, Elevated | 0.5 MPH (0.8 kmph) |
| Gradeability | 25% |
| Turning Radius - Inside | Zero |
| Turning Radius - Outside | 95.1" / 2.41 m |
| Tire Size | 16 x 5" / 406 x 125 mm |
| Tyre Type | Non-Marking Solid |
| Brakes (on drive wheels) | Electric, Friction |



SHERRIN
Rentals
AUSTRALIA WIDE
132 138

Email - info@sherrinrentals.com.au Web - www.sherrinrentals.com.au

26 Foot Scissor Lift